

A Donaldson Company

A WORLD LEADER IN FUME EXTRACTION TECHNOLOGY



DustPRO 1000 iQ

Last Updated on 09.04.2021



High performance dust and fume extraction system for industrial applications.

BOFA's DustPRO 1000 iQ high end dust extraction system combines extremely large filter capacity with high airflow and pressure rates, making it the ideal choice for heavy duty applications that generate large amounts of particulates.

Performance is enhanced with the inclusion of BOFA's acclaimed iQ Operating System taking performance and safety parameters to new levels and ensuring that maintenance, downtime and ownership costs are kept to a minimum.

More information about the Intelligent Operating System (iQ).

Intelligent

Operating System

(iQ)



HEPA filter



(RFA) technology



Automatic flow control (AFC) technology



Patented technology



ProTECT service plan



Technology

SureCHECK quality standard

Key features of the DustPRO 1000 iQ

iQ Operating System Standard

Reverse flow air filter technology Standard

Real time airflow reading Standard

'Run safe' operation Standard

Independent filter condition monitoring, display and warnings Standard High airflow and pressure rates Standard

Automatic flow control system Standard

High contrast display Standard

Remote diagnostics via USB Standard

HEPA filter Standard

Contact BOFA at https://bofainternational.com/en/contact/

https://bofainternational.com/en/portal/datasheets/dustpro-1000-iq/







Filters with long life and low replacement cost Standard

Filter change / system fail signal Optional

Remote stop / start interface Optional

Technical specification

1. iQ display 2. On / off switch 3. Power cable 4. Signal / interface cable 5. Castors 6. Door hinge 7. Hose inlet Connection -8. Exhaust outlet 125mm 9. Motor cooling inlet 10. Door latch **11.** Motor cooling outlet 12. Standby button 8 3 4 TR 而 D D C S 16 (6 6

Airflow through filters



Technical data

	EU	US	
Dimensions (HxWxD)	1205 x 615 x 790mm	47.44 x 24.21 x 31.10"	
Cabinet construction	Powder coated mild steel	Powder coated mild steel	
Airflow / Pressure	850m³/hr / 100mbar	500cfm / 100mbar	
Electrical data	230v Single-phase 1~ 50/60Hz Full load current: 12.8 amps / 2.2kw	115v 60/50Hz Full load current: 19.5 amps / 2.2kw	
Noise level	< 66dBA (at typical operating speed)	< 66dBA (at typical operating speed)	
Weight	100kgs	220.5lbs	
Approvals	UKCA and CE	cUL, UL*	

Bag pre-filter specfications			
Volume area	100ltrs approx		
Filter media	Polyester		
Filter media construction	8 pocket bag filter		
Surface media area	3.9m² approx (419.64 ft²)		
Filter efficiency	95% @ 0.9 microns		

HEPA filter specifications			
Surface media area	7.5m² approx (80.7 ft²)		
HEPA filter media	Borosilicate		
HEPA media construction	Maxi pleat construction with glue bead spacers		
Filter housing	Zintec mild steel		
Filter efficiency	99.997% @ 0.3 microns		

Unit part numbers					
Model	Voltage	Filter change / system failure signal	24V stop / start	Override	Part number
DustPRO 1000 iQ Powder coated	230V	No	No	No	30811619-1419
DustPRO 1000 iQ Powder coated	230V	Yes	Yes	Yes	6530811619-1419
DustPRO 1000 iQ Powder coated	115V	Yes	No	No	10810619-1419
DustPRO 1000 iQ Powder coated	115V	Yes	Yes	Yes	4660810619-1419

Replacement filters		
Model	Bag filter part number	HEPA filter part number
DustPRO 1000 iQ	A1030395	A1030394

* Tested to UL and cUL standards, but testing may be provided by alternate nationally recognised test laboratories. Certain product

configurations may affect the UL certification. Please speak to your sales representative.

Datasheet correct at time of publishing.

Where applicable, the carbon used in BOFA units is capable of removing a wide range of VOC's, however it is the responsibility of the user to ensure the carbon is suitable for their application. For specific applications, please contact us for details.

Think before you print! Please consider the environment before printing this document.

